

## **Easy to install**

Enjoy privacy with the simple design and easy installation











Compact design



Emergency charging



Status indicator



Hidden PIN code



Automatic locking





## Specifications

General Characteristics		Modes			Dual verification	
Material	Aluminum alloy	Operation mod	е	Manual mode	Alarm	Anti-prying alarm
Finishing	Electroplating			Auto mode		Outside forced lock alarm
	Baking varnishing	System unlock i	mode	General mode	Update	Batch update via rear interface
Color	Copper/Black		Dua	al verification mode	Indicator	Low battery indicator
Handle	_	Electrical Power				Lock status indicator
Mortise	_	Working power	r supply	4 AA batteries		Mute status indicator
	_	Battery life		10 months*		System lock indicator
Fingerprint sensor	Semiconductor	Emergency charging		5V power bank		Outside forced lock indicator
Connection	_	Operating Environment		Voice guide	Human voice guide	
Access Solution		Temperature		-20°C~+60°C		
Outside unlocking	Fingerprint	Humidity		15%RH~93%RH		
	PIN code	Installation Requirements				
	Card	Door thickness		30~50mm		
	_			50~90mm		
	_			Other range*		
Inside unlocking	Knob			<u> </u>		
	Button	Door swing	Left in	ward/Left outward		
	_	direction	Right inv	ard/Right outward		
Capacity		Door type	Woode	en/Copper/Security		
Fingerprint	100	Key Features				
Card	100	Lock		Indoor deadlock		
Master PIN code	1			System lock		
User PIN code	10	Safety		Hidden PIN code		
One-time PIN code	1		Outside	forced lock mode		

<sup>\* 10</sup> months: The laboratory data, the actual battery life will vary depending on the using scenes.

<sup>\*</sup> Other range: Please consult our service agent or an authorized dealer.