

PANACAST 50

Engineered to be the first new-normal-ready intelligent video bar.*

- › Unique 180° field of view keeps everyone in the picture at a safe distance
- › Virtual Director intelligently adjusts the video in real time for more immersive meetings
- › Safety Capacity and Room Usage Insights generates anonymous room occupancy data for all your meeting rooms at once
- › Network-connected system enables easy remote management
- › Real-time whiteboard streaming for more inclusive remote collaboration
- › Uniquely advanced system architecture powers a range of intelligent features
- › Plug-and-play for fast set-up and maximum ease of use
- › Intelligent Zoom automatically adjusts the field of view to include everybody in the conversation



TECHNICAL SPECIFICATIONS

| | | |
|----------------------------|-------------------------------------|--|
| General info | Box contents | PanaCast 50, Power supply, Wall mount, USB-C to USB-A cable 2m/6.6ft (USB 3.0) |
| | Packaging dimensions (WxHxD) | 685mm x 167mm x 130mm 27in x 6.6in x 5.1in |
| | Main unit dimensions (WxHxD) | 650mm x 80mm x 125mm 25.6in x 3.1in x 4.9in |
| | Weight | 2200g 77.6oz |
| | Certifications and compliance | Microsoft Teams, Microsoft Teams Rooms (with separate Microsoft Teams Rooms certification for integrated Content Camera), Zoom Rooms, Zoom |
| Video | Number of cameras | 3 |
| | Type of camera | Panoramic multi-camera array |
| | Camera resolution | 13 megapixels |
| | Zoom | Up to 6x lossless digital zoom |
| | Field of view | Horizontal: 180°, Vertical: 54° |
| | Resolution | Panoramic-4K: 3840 x 1080 @ 30 fps |
| | Intelligent zoom | Yes |
| | Virtual director | Yes |
| Audio | Vivid HDR | Yes |
| | Speakers | 2 x 2" (50mm) woofers, 2 x 3/4" (20mm) tweeters |
| | Speaker frequency range | 80Hz - 20000Hz |
| | Number of speakers | 4 |
| | Automatic Speaker Detection | Yes |
| | Microphone type | 8 microphone beamforming array |
| | Number of microphones | 8 |
| | Microphone sensitivity | -37dBFS |
| | Microphone frequency range | 100Hz - 8000Hz |
| Microphone bandwidth | 100Hz - 8Hz | |
| Software & Apps | System requirements | Compatible with Windows 10, compatible with macOS 10.15 and later, including macOS 11.x |
| | Compatible software and apps | Jabra Direct, Jabra Sound+, Jabra Xpress |
| | Integrated PeopleCount | Yes |
| | Software Development Kit (SDK) | Yes |
| | Whiteboard Sharing / Content Camera | Yes |
| Ease of use | Manual Pan-Tilt-Zoom (PTZ) | Yes |

TECHNICAL SPECIFICATIONS

| | | |
|----------------------|------------------------|-------------------------------|
| Connectivity | Connectivity | USB, USB-C, Ethernet (RJ45) |
| | Supported USB versions | USB 2.0, USB 3.0 |
| Extended info | Operating temperature | 5°C to 35°C 41°F to 95°F |
| | Storage temperature | -20°C to 60°C -4°F to 140°F |

| PRODUCT TYPE | SKU | DESCRIPTION |
|--------------------|----------|---|
| Products | 8200-237 | Jabra PanaCast 50 - Black |
| | 8201-237 | Jabra PanaCast 50 - Grey |
| Accessories | 14202-10 | Jabra PanaCast 50 USB Cable - USB 3.0, 2m |
| | 14202-11 | Jabra PanaCast 50 USB Cable - USB 2.0, 5m |
| | 14202-12 | Jabra PanaCast USB Cable (3m) |
| | 14207-70 | Jabra PanaCast 50 Table Stand - Black |
| | 14207-71 | Jabra PanaCast 50 Wall Mount - Black |
| | 14207-72 | Jabra PanaCast 50 Screen Mount |
| | 14207-75 | Jabra PanaCast 50 Table Stand - Grey |
| | 14207-76 | Jabra PanaCast 50 Wall Mount - Grey |
| | 8211-209 | Jabra PanaCast 50 Remote - Grey |
| | 8220-209 | Jabra PanaCast 50 Remote - Black |

* jabra.com/commercial-claims

Mua thiết bị hội nghị truyền hình Jabra tất cả trong một giá rẻ tại:
CÔNG TY TNHH CUNG ỨNG NGỌC THIÊN
Điện thoại: 028 777 98 999
Email: info@vnsup.com