## MAXHUB® UC M31 Camera

## 180° Plug And Play Ready.



## MAXHUB UC M31 180 Degree 4K Web Camera

The MAXHUB UC M31 is the perfect camera for small to large conference rooms. The camera employs new video layouts that let you switch views quick and easy. Get up and running fast with a simple plug and play system. With advanced panoramic camera stitching algorithms, MAXHUB the M31 allows users to see the entire room in picture perfect clarity. The hardware in the cameras boast an 1/2.8" SONY sensor while the software does it even better with the ability to track the speaker, adjust frame of view, and be controlled remotely via RDP technology. The best web camera on the market should also come equipped with a warranty to match, which MAXHUB has implemented in their entire UC line with a 3-Year Hot Swap Policy.



## MAXHUB UC M31 180° CAMERA

**SPECIFICATIONS** —

CAMERAS		MI	CROPHONES	CONNECTION		
tity	3x 120° Cameras	Quantity	2			
or	1/2.7" CMOS	Signal To Noise Ratio	65dB	USB-A (Host)	1	
Is	12MP Per Camera					
ure	2.2 <sub>f</sub>	Range	0~4m	USB-C (Device)	1	
	3840x2160 @24fps 3840x1376 @30fps	Response Frequency	200 Hz to 8 kHz			
utput	3840x962 @30fps 1920x1080 @30fps					
m FOV	180° H x 54° V					
OPERATING SYSTEMS		DIMENSIONS		ENVIROMENTAL		
Windows 10 or Higher  10.13 or Higher		Product (L x W x H)	5.8" x 1.3" x 3"	Operation Temp (°F)	32°F - 104°F	
1	0.13 or Higher	Package	7" x 7" x 2"	Operation	10-90% Room Humidity	
		Net Weight	.48 lbs(0.22Kg)	Humidity	10-90 % Room numberly	
		Gross Ibs	1.2 lbs(0.55Kg)	Altitude	<5000M	
	tity or Is ure utput n FOV	3x 120° Cameras   1/2.7" CMOS     1s	tity 3x 120° Cameras for 1/2.7" CMOS Is 12MP Per Camera ure 2.2 3840x2160 @24fps 3840x1376 @30fps 3840x962 @30fps 1920x1080 @30fps 1920x1080 @30fps Windows 10 or Higher  10.13 or Higher  Publication  Quantity Signal To Noise Ratio Pickup Range Response Frequency  Response Frequency	Cor	Quantity   2   USB-A (Host)	

USAGE ———

SOFTWARE		COMPATIBILITY		MANAGEMENT		WARRANTY	
Brightness	Yes	ZOOM	Yes	FOV Button	Yes	HOT SWAP	3-Years Limited
3D Noise	Yes	Cisco Webex	Yes	Desktop	Mac and Windows	3	Year
Reduction		Skype	Yes			4	1001
Contrast	Yes	Teams	Yes			Hot Wa	t-Swap rranty
Exposure	-2~+2						
Stroboscopic	Automatic,						
suppression	50Hz/60Hz						_

SETUP ——

WHAT'S IN THE BOX		SETUP		STATEMENT	
Power Adapter	1	Plug-and-Play	Yes	SIZE AND WEIGHT VARY BY CONFIGURATION AND MANUFACTURING PROCESS, PLEASE REFER TO THE ACTUAL PRODUCT. THE PRODUCT IMAGES ARE FOR ILLUSTRATIVE PUR- POSES ONLY AND MAY SLIGHTLY DIFFER IN APPEARANCE. COLOUR. SIZE, ETC. FROM THE	
USB Cable	1			ACTUAL PRODUCT. THE DESCRIPTION, ILLUSTRATIONS, ETC. IN THIS DOCUMENT MAY SUBJECT TO CHANGE IN ACCORDANCE WITH THE LATEST PRODUCT SPECIFICATION	
User Manual	Yes			AND PERFORMANCE. SHOULD THE ABOVE-MENTIONED CHANGE IN THE DOCUMENT BECOME NECESSARY, THE DOCUMENT MAY BE UPDATED WITHOUT WRITTEN NOTICE.	



