

# JABRA SPEAK™ 810

Conference Calls Made Simple; Collaboration Made Easy



Works with any *Bluetooth* enabled device

- Intended for 15 meeting room attendees
- Unique ZoomTalk™ Microphones
- USB charge out port



| FEATURE                               | BENEFIT  |
|---------------------------------------|--|
| Packaging dimensions                  | H 456 x L 287 x W 366 mm   |
| Weight mono / duo                     | 965g (1570g include packaging)   |
| Whats in the box                      | Jabra SPEAK 810, Charger (incl. PE bag), Exchangeable pins (4 pcs), Warning leaflet, Warranty leaflet, Quick Start Guide, Korean leaflet, Foam bag, Tape, Silica bag   |
| Battery included                      | No   |
| AC power supply                       | Yes  |
| Certifications                        | Regulatory Approvals: CE, FCC, IC, EAC, RRC, CCC, RCM, KCC, TELEC, iDA, NCC, RoHS, REACH, ETA, SIRIM, SDPPI, RCM, NTC<br>Industrial Certifications: Bluetooth 4.1, Skype for Business, Cisco, Avaya, Mitel, Alcatel, Unify   |
| Warranty                              | 2 years  |
| Bluetooth device                      | Yes  |
| DECT Device                           | No   |
| NFC                                   | Yes  |
| Operating range                       | Up to 30m/100ft  |
| Headset bandwidth                     | Wideband   |
| Connection (mini jack, USB, etc)      | USB/Bluetooth/3.5 mm jack  |
| What is Bluetooth wireless technology | Bluetooth version 4.1  |
| Speaker Size                          | L 56 x W 56 x H 28mm   |
| Speaker sensitivity                   | 80±2dB@1W/1m   |
| Speaker impedance                     | 4 ohm  |
| Speaker Max Input Power               | 6W   |
| Speaker Frequency Range               | 100Hz – 20KHz  |
| Microphone type                       | Digital MEMS, bottom port  |
| Microphone Sensitivity                | VDD=1.8V, FCLK =2.4MHz, (0dBFS2=1V/Pa@1kHz), Min-29dB, Normak: -26dB, Max -23dB  |
| Microphone Frequency Range            | 20Hz – 8K Hz   |
| Supported Bluetooth profiles          | A2DP (v1.2), Hands Free Profile (v1.6), Headset Profile (v1.2), AGHFP (v1.6)   |
| Bluetooth wireless technology         | Bluetooth 4.1  |
| Speaker bandwidth Music mode          | HiFi   |
| Speaker bandwidth Speak mode          | Wideband   |
| Microphone bandwidth                  | Wideband   |
| Cord length                           | USB Cord Length: 2.1 m, 3.5mm jack Cord length 1.2m  |
| Operating temperature                 | -10 °C to + 50 °C  |
| Storage temperature                   | -30 °C to + 80 °C Storage temperature range: (-20°C to +35°C 6 months), (+35°C to +45°C 3 months), (+45°C to +45°C 1 month), (+60°C to +70°C 1 hour with no degradation), (+70°C to +85°C max. 1 hour (<20% degradation)   |
| Supported modes                       | SCO, eSCO, Sniff mode  |
| Security                              | Pairing, Authentication and Encryption (Bluetooth standard)  |
| Paired devices                        | Up to 900 trusted devices  |
| Power consumption speaker             | 6W   |
| Features                              | ZoomTalk™ microphone with adaptive array 5 m/15 ft. range (15 persons), Microphone focus (zoom on the person speaking) Connectivity: USB, BT/NFC & 3.5mm jack (AUX), USB charge out for tablets and mobile phones, Kensington lock slot, Intuitive on-device call-controls and indicators for true UC experience, Plug & play for all smart device and all communication platforms |

| SKU      | DESCRIPTION        | EAN CODE      |
|----------|--------------------|---------------|
| 7810-109 | Jabra SPEAK 810 MS | 5706991018448 |
| 7810-209 | Jabra SPEAK 810 UC | 5706991019308 |
| 7810-199 | Jabra SPEAK 810 MS | 5706991019308 |
| 7810-299 | Jabra SPEAK 810 UC | 5706991019315 |