

VPL-FHZ60

5,000 lumens WUXGA laser light source projector (color availability may vary by country)



Overview

Bright, beautiful images with low running costs, minimal maintenance and flexible installation

The VPL-FHZ60 laser projector is ideal for a wide range of business, education, and entertainment applications. The powerful Z-Phosphor laser light source is teamed with Sony's advanced BrightEra 3LCD projection engine to deliver extremely bright, detail-packed WUXGA resolution images with a generous 5,000 lumens of brightness, and rich, stable colors. Constant Bright maintains the same brightness throughout the 20,000 hours recommended lifespan.

The laser light source allows up to 20,000 hours* of virtually zero-maintenance operation without the worry of sudden lamp failures. A new automated filter system cuts the hassle of regular dust cleaning. Near-zero maintenance needs are complemented by a range of energy-saving features, significantly driving down total lifetime ownership costs.

Offering a stylish new blend-in design, tidy cable management, and low fan noise, the VPL-FHZ60 fits smoothly into almost any environment — from academic institutions, corporate, medical training, and public sector organizations to visitor attractions and retail spaces. Seamlessly blend images from multiple projectors to create super-sized displays, or accurately project proportioned images onto angled or curved surfaces. Mount the projector at any angle, even on its side or upside down. Setup is easier than ever with a friendly new installation menu.

The VPL-FHZ60/W is a white model.

VPL-FHZ60/B is a black model.

Black and lensless models available in Europe; please check for local availability.

*Actual hours may vary depending on usage environment.

Features

Very high image quality with Sony's advanced BrightEra 3LCD projection engine and Z-Phosphor laser light source

The Z-Phosphor laser light source is coupled with Sony's acclaimed BrightEra 3LCD projection engine to ensure high 5000 lumen image brightness with vivid, natural color reproduction.

Constant Brightness

Constant Bright Maintains the same brightness throughout the 20,000 hours recommended life span.

Advanced picture refinement technologies

Picture quality is boosted by advanced processing featured on Sony home cinema projectors. Reality Creation uses a powerful pattern-matching database to optimize every pixel. Contrast Enhancer actively analyzes and refines dark and light image areas for sparkling highlights and rich, deep blacks.

Crisp, detail-packed WUXGA resolution images

See the finest detail in PC presentations, videos or multimedia signage with WUXGA (1920 x 1200) 16:10 resolution.

Up to 20,000 hours* operation with virtually no maintenance

The advanced laser light source offers up to 20,000 hours* operation without lamp exchange, reducing lifetime running costs compared with traditional projectors.

*Actual hours may vary depending on usage environment.

Hassle-free automatic filter cleaning

Focus on great-looking images instead of arduous maintenance tasks: new automated filter cleaning system removes dust every 100 hours.

Energy saving features

Reduce running costs even further with convenient energy-saving features: Picture Mute and Auto Dimming.

Save time with every presentation

Quick power On/Off dramatically cuts warm-up time after switch-on

before you can start presenting at full brightness.

360° free-angle installation capability

Enjoy greater installation flexibility: position the projector freely at any angle – or its side or even upside down.

Powered Wide Lens Shift

Generous lens shift adjustments give more flexibility for positioning the projector where you need it: close to ceilings or even horizontally offset.

Included powered standard zoom lens plus wide choice of lens options

Installation flexibility is increased by a wide range of compatible lens options to suit virtually any size of room and throw requirements. New quick-release bayonet mount simplifies quick lens exchange.

Supports HDBaseT

Simpler, more cost-effective installation and connectivity with digital transmission of HD video, audio and networking/control over a single Ethernet cable.

Create super-size displays with Edge Blending

Seamlessly join accurately color-matched images from multiple projectors, simplifying creation of stunning super-size displays for corporate and education.

Project onto non-flat surfaces with Image Warping

Easily correct image geometry for natural-looking projections – even on convex or concave surfaces. Corner and edge correction can be easily adjusted with the supplied remote and on-screen menu.

Quiet operation

Low fan noise ensures discreet, unobtrusive operation in quiet environments from museums and galleries to lecture theaters.

Slim, attractive new blend-in design

The slim, stylish case design features a flat top surface that blends in discreetly when the projector is ceiling mounted. The clean appearance is accentuated by a new terminal cover that reduces cable clutter.

Picture Mode

New Picture Mode ensures great-looking pictures in any presentation conditions. Select Standard, Dynamic, Brightness Priority or Multi Screen mode for optimized image quality, with any source and in every room.

Simple set-up with friendly new Installation menu

Easily adjust projector settings with remote commander, including warping and edge blending.

Project Side by Side

Project images from two inputs at the same time: ideal for applications such as video conferencing and medical training where two images need to be seen simultaneously.

Specifications

Display system

Display system 3 LCD system

Display device

Size of effective display area 0.76" (19 mm) x 3 BrightEra LCD Panel, Aspect ratio: 16:10

Number of pixels 6,912,000 (1920 x 1200 x 3) pixels

Projection lens *1

Focus Powered

Zoom - Powered/Manual Powered

Zoom - Ratio Approx. x 1.6

Throw ratio 1.39:1 to 2.23:1

Lens shift - Powered/Manual Powered

Lens shift - Range Vertical -5%, +60%

Lens shift - Range Horizontal +/- 32%

Light source

Type Laser diode

Filter cleaning / replacement cycle (Max.)*2

Filter cleaning / replacement cycle (Max.) 20000 H (service maintenance)

Screen size

Screen size 40" to 600" (1.02 m to 15.24 m) (measured diagonally)

Light output

Mode: High 5000 lm

Mode: Standard 3500 lm

Color light output

Mode: High 5000 lm

Mode: Standard 3500 lm

Contrast ratio (full white / full black) *3

Contrast ratio (full white / full black) 10000:1

Displayable scanning frequency

Horizontal 15 kHz to 92 kHz

Vertical 48 Hz to 92 Hz

Display resolution

Computer signal input Maximum display resolution: 1920 x 1200 dots *4

Video signal input NTSC, PAL, SECAM, 480/60i, 576/50i, 480/60p, 576/50p, 720/60p, 720/50p, 1080/60i, 1080/50i

The following items are available for digital signal (HDMI input) only; 1080/60P, 1080/50p, 1080/24p

Color system

Color system NTSC3.58, PAL, SECAM, NTSC4.43, PAL-M, PAL-N, PAL60

Keystone correction (Max.)

Horizontal +/- 30 degrees

Vertical +/- 30 degrees

INPUT OUTPUT (Computer/Video/Control)

INPUT A RGB / Y PB PR input connector: Mini D-sub 15 pin (female)
Audio input connector: Stereo mini jack

INPUT B DVI input connector: DVI-D 24-pin (single link), HDCP support
Audio input connector: Shared with input A

INPUT C HDMI input connector: HDMI 19-pin, HDCP support
Audio input connector: HDMI audio support

INPUT D HDBaseT interface connector: RJ45, 4 play (Video, Audio, LAN, Control)

VIDEO IN Video input connector: BNC
Audio input connector: Shared with input A

OUTPUT A Monitor output for Input A Connector: Mini D-sub 15-pin (female)
Audio output connector: Stereo mini jack

OUTPUT B Monitor output for Input B Connector: DVI-D 24-pin (single link), HDCP not supported
Audio output, Monitor out connector: Stereo mini jack

REMOTE D-sub 9-pin (male) / RS232C

LAN RJ45, 10BASE-T/100BASE-TX

IR
(Control S) Stereo mini jack, Plug in power DC5V

Acoustic Noise

Lamp mode: Standard 28 dB

Operating temperature / Operating humidity

Operating temperature / Operating humidity 0°C to 40°C (32°F to 104°F) / 20% to 80% (no condensation)

Storage temperature / Storage humidity

Storage temperature / -10°C to +60°C (14°F to +140°F) / 20% to
Storage humidity 80% (no condensation)

Power requirements

Power requirements AC 100 V to 240 V, 4.5 A to 1.9 A, 50 Hz / 60 Hz

Power consumption

AC 100 V to 120 V Mode: High: 420 W

AC 220 V to 240 V Mode: High: 408 W

Power Consumption (Standby Mode)

AC 100 V to 120 V 0.5W (when "Standby mode" is set to "Low")

AC 220 V to 240 V 0.5W (when "Standby mode" is set to "Low")

Power Consumption (Networked Standby Mode)

	15.0 W (LAN)
AC 100 V	15.0 W (HDBaseT)
to 120 V	15.0 W (All Terminals and Networks Connected) (when "Standby Mode" is set to "Standard")
	13.3 W (LAN)
AC 220 V	13.3 W (HDBaseT)
to 240 V	13.3 W (All Terminals and Networks Connected) (when "Standby Mode" is set to "Standard")

Standby Mode / Networked Standby Mode Activated

Standby Mode / Networked Standby Mode Activated	Approx. 10 Minutes
--	-----------------------

Heat dissipation

AC 100 V to 120 V 1433 BTU/h

AC 220 V to 240 V 1393 BTU/h

Dimensions (W x H x D)

460 x 169 x 515 mm

Dimensions (W x H x D) (without protrusions)

18 1/8 x 6 21/32 x 20 9/32 inches

Mass

Mass 16 kg (34 lb)

Supplied accessories

Remote commander RM-PJ27

Optional accessories

Projection Lens VPLL-3007 / Z3009 / Z3024 / Z3032

Notes

*1 With supplied standard lens

This figure is expected maintenance time, not guaranteed time. The

*2 actual value depends on the environment and how the projector is used.

*3 The value is average.

*4 Available for VESA Reduced Blanking signal.

Gallery























