PUBLIC ADDRESS / SPEAKERS / EXPONENTIALS

FE-1310

LOW IMPEDANCE HORN SPEAKER





Suitable for indoor and outdoor PA installations It allows you to cover large areas and distances



Includes stainless steel mount

ESPECIALLY RECOMMENDED IN:









Factories

Sports facilities

Education

All sectors



+ Info:

https://fonestar.com/FE-1310

FONESTAR

Poligono Trascueto. 39600 Revilla de Camargo. Cantabria (España)



DESCRIPTION

Low impedance horn loudspeakerConstructed of ABS, aluminium and with stainless steel screws and mount. Water protection (IP-66) Suitable for indoor and outdoor PA installations. Excellent frequency response, perfect for public address applications. With an angle of coverage and sensitivity which allow the reach of great distances and coverage of large areas. Mount for easy installation, minimizing assembly time. For public address installations in large areas, sports facilities, industrial buildings, shopping centres, schools, hospitals, etc.

TECHNICAL CHARACTERISTICS

FEATURES	Low impedance horn speaker.
POWER	30 W RMS
RESPONSE	250-12,500 Hz
IMPEDANCE	8 Ohm
SENSITIVITY	107 dB at 1 W/1 m
DISPERSION	130°
PROTECTION	IP-66
MATERIAL	ABS/Aluminium Stainless steel screws and mount.
COLOUR	Ivory (RAL 1014,RAL 1015)
DIMENSIONS	26 cm Ø x 26 cm depth
WEIGHT	1.5 kg



+ Info:

https://fonestar.com/FE-1310