



CCS-Dx CCS Delegate Unit



The CCS-Dx CCS Delegate Units enable delegates to actively take part in the proceedings. A built-in microphone allows them to speak to the other delegates, and they can listen to the discussion using the built-in loudspeaker or (optional) personal headphones.

Functions

Possible-To-Speak

A so called 'Possible-To-Speak' indicator is built-in showing if it is possible to switch on the microphone. This functionality is shown by a white LED combined with the 'microphone on' indicator.

Microphone with flexible stem and light ring

The microphone is mounted on a flexible stem, which is easily adjustable to suit personal preferences. It also allows two people to use the same delegate unit as they can pull the microphone towards them when required to speak. Incorporated into the head of the microphone is a light ring which illuminates red to indicate when the microphone is on.

Built-in loudspeaker

Loudspeaker volume is set centrally at the Control Unit for all delegate units. To prevent acoustic feedback, the built-in loudspeaker is automatically muted when the microphone is on.

- ▶ **Unique, patent pending "Possible-To-Speak" indicator**
- ▶ **Compact, attractive design**
- ▶ **Built-in volume control for headphones**
- ▶ **Microphone with flexible stem and light ring**
- ▶ **Two headphone sockets**
- ▶ **Available with standard or extended length microphone stems**

Two headphone sockets

Two 3.5 mm (0.14 in) stereo headphone sockets (wired for mono) allow two pairs of headphones to be connected so two delegates can simultaneously use the unit. It is also possible to connect a tape recorder to one headphone socket, and use the other headphone socket to listen to the proceedings.

Built-in volume control for headphones

The headphone volume level can be adjusted by means of a thumbwheel on the unit for maximum comfort.

Compact, attractive design

Featuring modern, unobtrusive styling and finished in charcoal gray these units make a valuable addition to any venue.

Standard or Extended Length Microphone Stems

The delegate units are available with standard 313 mm (12.3 in) or extended 488 mm (19.2 in) microphone stem lengths.

Controls and Indicators

- Microphone on/off button
- Rotary volume control for adjusting headphone volume
- Loudspeaker, automatically muted when microphone is on and/or headphones are connected
- Possible-To-Speak indicator (white LED)
- Microphone 'on' indicator (red LED)
- Light ring indicator on microphone stem, lights up red when microphone is on

Interconnections

- 1 x 2 m (78.7 in) cable terminated with a 7-pole male connector for loop-through connection to other delegate or chairman units, or to a Control Unit
- 1 x 7-pole circular female connector for loop-through connection to other delegate or chairman units
- 2 x 3.5 mm (0.14 in) stereo headphone sockets

Technical Specifications**Mechanical**

Dimensions unit without microphone (H x W x D)	71 x 220 x 140 mm (2.8 x 8.7 x 5.5 in)
--	--

Height with microphone in horizontal position	134 mm (5.3 in)
---	-----------------

Length of microphone from mounting surface	CCS-DS	CCS-DL
	313 mm (12.3 in)	488 mm (19.2 in)

Weight	approx. 1 kg (2.2 lb)
--------	-----------------------

Mounting	tabletop (portable or fixed)
----------	------------------------------

Material (top)	polymer
----------------	---------

Material (base)	painted metal
-----------------	---------------

Color (top)	charcoal (PH10736)
-------------	--------------------

Color (base)	charcoal (PH10736)
--------------	--------------------

Ordering Information

CCS-DS CCS Delegate Unit Short	CCS-DS
Microphone	
microphone stem length 313 mm (12.3 inch)	

CCS-DL CCS Delegate Unit Long	CCS-DL
Microphone	
microphone stem length 488 mm (19.2 inch)	

Accessories

DCN-DISCLM Cable Clamp (25 pcs)	DCN-DISCLM
25 pieces	

Americas:
 Bosch Security Systems, Inc.
 130 Perinton Parkway
 Fairport, New York, 14450, USA
 Phone: +1 800 289 0096
 Fax: +1 585 223 9180
 security.sales@us.bosch.com
 www.boschsecurity.us

Europe, Middle East, Africa:
 Bosch Security Systems B.V.
 P.O. Box 80002
 5600 JB Eindhoven, The Netherlands
 Phone: +31 40 2577 284
 Fax: +31 40 2577 330
 emea.securitysystems@bosch.com
 www.boschsecurity.com

Asia-Pacific:
 Robert Bosch (SEA) Pte Ltd, Security Systems
 11 Bishan Street 21
 Singapore 573943
 Phone: +65 6571 2600
 Fax: +65 6571 2698
 apr.securitysystems@bosch.com
 www.boschsecurity.com

Represented by