



CS-1DU

Order No.: 0173080

PRODUCTINFOS

Conference System CS-1

Your opinion will be heard! The control unit CS-1CU, the microphone station for the chairperson CS-1CH and the microphone station for conference delegates CS-1DU together form a conference system with extensive configuration facilities for maximum flexibility.

Microphone station for conference delegates

- Back electret cartridge with cardioid polar pattern, optimised for voice transmissions
- Low-distortion speaker
- Operation via function button
- Headphone connection
- Status displays at microphone and desktop station

AV-views 02/2010

“A solid and reliable conference system which provides a very clear voice transmission.”

TECHNICAL SPECIFICATIONS

CS-1DU

Description	microphone station for conference delegates
Transmission method	cable
Polar pattern	cardioid
System	back electret
Audio frequency range	50-18,000 Hz
Power supply	via control unit CS-1CU
Gooseneck length	400 mm
Admiss. ambient temp.	0-40 °C
Dimensions	115 x 65 x 170 mm (console housing)
Weight	1.1 kg
Cable	2 m
Connection	2 x 3.5 mm jack 1 x 2 m connection cable with 7-pole DIN plug 1 x 7-pole DIN jack
Packing dimensions (W x H x L)	0.16 x 0.14 x 0.41 m
Gross weight	1.551 kg
Net weight	1.096 kg