



RingCentral

POLY STUDIO X30 FOR RINGCENTRAL



X30



VIDEO CONFERENCING, MEET RADICAL SIMPLICITY

BENEFITS

- Get any huddle or small room up and running in minutes, with a simple setup process and all-in-one design
- Make it easy for anyone, even guests, to share content wirelessly from any personal device—with no special apps or tools needed
- Powerful audio pickup and incredible noise blocking technology allows every word to be heard without distractions
- On-board support for RingCentral means no room PC or Mac is required

POLY STUDIO X30

The Poly Studio X30 video bar delivers radical simplicity in a small, elegant package. In small- and medium-sized rooms, connect to your RingCentral meetings with one touch. Experience full boardroom-quality audio, advanced camera capabilities, and quick wireless content—all in one sleek video bar. And say goodbye to unnecessary pucks, cords, and cables, along with the PC or Mac to drive the meeting, since the RingCentral App is built right in. Easy to install, easy to manage.

- Ideal for huddle to small sized rooms
- Compact, lightweight design easily fits on top or underneath display
- Affordable price delivers excellent huddle room performance without breaking the bank

POLY STUDIO X30



SPECIFICATIONS

PACKAGE INCLUDES

- Poly Studio X30
- Cable bundle
- Monitor clamp
- Privacy cover

VIDEO INPUT

- 1x HDMI

VIDEO OUT

- 1x HDMI
- Touch display compatible

PEOPLE VIDEO RESOLUTION

- Supports 720p @ 24fps

CONTENT VIDEO RESOLUTION

- Supports 1080p @ 15fps

CONTENT SHARING

- Input
- Wireless Screen Sharing

CAMERA

- 5x digital zoom
- 120° FOV
- UHD 2160p (4K) capture resolution
- Automatic people framing
- Automatic speaker tracking

AUDIO INPUT

- 4x MEMS microphones
- Microphone pickup range up to 15 ft

AUDIO OUTPUT

- Single speaker

OTHER INTERFACES

- 1x USB-A (3.0)
- 1x USB-C

AUDIO STANDARDS AND PROTOCOLS

- Opus
- SILK
- G.722

NETWORK

- IPv4
- IPv6
- 1x 10/100/1G Ethernet
- Auto-MDIX
- Web proxy support
 - Basic
 - Digest
 - NTLM
- Simple Certificate Enrollment Protocol (SCEP)

SECURITY

- Authenticated access to admin menus, web interface, and API
- Local account password policy configuration
- Security profiles
- Local account and login port lockout
- Secure defaults
- Remote logging with support for TLS

OPTIONS SOLD SEPARATELY

- VESA and wall mount kit
- Stand
- Poly TC8
- Poly Trio
- Inverted mount kit

INTEROPERABILITY

- Certified for RingCentral
- USB device mode

ELECTRICAL

- Auto sensing power supply
- Typical operating voltage/power
 - 37 VA @ 120 V @ 60 Hz
 - 37 VA @ 230 V @ 50/60 Hz
- Typical BTU/h
 - 65

ENVIRONMENTAL SPECIFICATION

- Operating temperature
 - 0 to 40 °C
- Operating humidity (non-condensing)
 - 15 to 80%
- Non-operating temperature
 - -40 to 70 °C
- Non-operating humidity (non-condensing)
 - 5 to 95%
- Maximum altitude
 - 16,000 ft

PHYSICAL CHARACTERISTICS

- 17.39 W x 2.46 H x 2.42 D (inches)
441.8 W x 62.5 H x 61.6 D (mm)
- 1.6 lbs/.73 kg

LIMITED WARRANTY

- One year Limited Warranty per www.poly.com/us/en/legal/warranty

*Supported in future software update.

LEARN MORE

For more information on Poly Studio X30, visit www.poly.com/studiox