

# Cisco Catalyst 8200 Series Edge Platforms

---

# Contents

Product overview	3
Platform details	4
Platform Performance	5
Overall platform benefits	6
Supported modules	9
Memory, storage, and accessory options	11
Optics and transceivers modules	12
Power supplies	12
Software requirements	13
Licensing	15
Specifications	15
Ordering information	17
Product sustainability	17
Services	18
Cisco Capital	19
For more information	19
Document history	20

The Cisco Catalyst 8200 Series Edge Platforms are 5G-ready cloud edge platforms designed for Secure Access Service Edge (SASE), multilayer security, and cloud-native agility to accelerate your journey to cloud.



The Cisco® Catalyst® 8200 Series Edge Platforms with Cisco IOS® XE SD-WAN software deliver Cisco’s secure, cloud-scale SD-WAN and SD-Routing solutions to the small branch. The platforms are purpose-built for performance and integrated SD-WAN services along with flexibility to deliver security and networking services together from the cloud or on premises. They have a wide variety of interface options to choose from, with backward compatibility to existing WAN, LAN, and voice modules. Powered by Cisco IOS XE, a fully programmable software architecture, and API support, the Catalyst 8200 Series can facilitate automation at scale in both SD-WAN and SD-Routing deployments to achieve zero-touch IT capability while migrating workloads to the cloud. The platforms also come with a trustworthy solutions 2.0 infrastructure that secures them against threats and vulnerabilities through advanced integrity verification and remediation of threats.

The 8200 Series is well suited for small and medium-sized enterprise branch offices at optimal price/performance with integrated SD-WAN and SD-Routing services.

The Catalyst 8200 Series Edge Platforms are offered in two models: C8200L-1N-4T for the small branch with SASE-compliant, cloud-based security requirements, and C8200-1N-4T for the small to medium-sized branch with requirements for higher throughput, scale, and service flexibility. In addition to supporting SASE-compliant cloud-based security services, the C8200-1N-4T also delivers a flexible system of best-in-class, on-premises security services through container-based apps, using Cisco’s third-party ecosystem.

## Product overview

### Product highlights

**Table 1.** Product highlights

Product feature	Benefits and description
<b>Multicore processors</b>	<ul style="list-style-type: none"> <li>• C8200-1N-4T uses an 8-core Intel® x86 CPU with 8 GB DRAM memory default</li> <li>• C8200L-1N-4T uses a 4-core Intel® x86 CPU with 4 GB DRAM memory default</li> <li>• High-performance multicore processors support high-speed WAN connections</li> <li>• Dynamic core allocation architecture will repurpose unused cores into forwarding entities as per the user’s configuration</li> </ul>
<b>Embedded IPsec VPN hardware acceleration</b>	<ul style="list-style-type: none"> <li>• C8200-1N-4T enables up to 1 Gbps IPsec traffic</li> <li>• C8200L-1N-4T enables up to 500 Mbps IPsec traffic</li> <li>• Increases scalability for IPsec throughput requirements</li> <li>• SSL and crypto hardware acceleration</li> </ul>
<b>Integrated Gigabit Ethernet ports</b>	<ul style="list-style-type: none"> <li>• Provides four built-in Ethernet WAN ports</li> <li>• Two Ethernet ports are Small Form-Factor Pluggable (SFP) and two are RJ45 ports, enabling fiber as well as copper connectivity</li> </ul>

Product feature	Benefits and description
<b>DRAM</b>	<ul style="list-style-type: none"> <li>• C8200-1N-4T ships with 8 GB DRAM</li> <li>• C8200L-1N-4T ships with 4 GB DRAM</li> <li>• C8200-1N-4T can be upgraded to 16 GB and 32 GB DRAM for higher scale and performance</li> <li>• C8200L-1N-4T can be upgraded to 8GB, 16 GB and 32 GB DRAM for higher scale and performance</li> </ul>
<b>Flash memory support</b>	<ul style="list-style-type: none"> <li>• Both models have an integrated onboard 8-GB flash which is not upgradable. M.2 storage provides flash upgrade options</li> </ul>
<b>M.2 storage</b>	<ul style="list-style-type: none"> <li>• The C8200-1N-4T is shipped with default 16G M.2 storage and can be upgraded to 32G M.2 USB and 600G M.2 Non-Volatile Memory Express (NVMe) Storage</li> <li>• The C8200L-1N-4T does not ship with a default M.2 storage but can be upgraded to 16G, 32G USB and to 600G M.2 Non-Volatile Memory Express (NVMe) Storage</li> </ul>
<b>Power supply</b>	<ul style="list-style-type: none"> <li>• Both models use an internal, fixed AC power supply</li> <li>• Power over Ethernet (PoE) is available as an option</li> <li>• PoE ports added in the Network Interface Module (NIM) slot will require an additional external PoE power supply</li> </ul>
<b>Modularity and form factor</b>	<ul style="list-style-type: none"> <li>• 1-Rack Unit (1RU) form factor</li> <li>• Supports NIM and Pluggable Interface Module (PIM) slots</li> </ul>
<b>Integrated security</b>	<ul style="list-style-type: none"> <li>• Hardware-anchored Secure Boot and Secure Unique Device Identification (SUDI) support for Plug and Play to verify the identity of the hardware and software</li> </ul>

## Platform details

### Models and configurations



**Figure 1.**  
Catalyst 8200 Series with 1 NIM slot and 4x 1 Gigabit Ethernet WAN ports

Tables 2 and 3 detail platform specifications and performance, respectively.

**Table 2.** Platform specifications

Model	Description	1G port density	Slots	Memory (DRAM) default	Storage (M.2 SSD) default
<b>C8200-1N-4T</b>	C8200 1RU w/ 1 NIM slot and 4x 1 Gigabit Ethernet WAN ports	4	1 NIM 1 PIM	8 GB	16 GB
<b>C8200L-1N-4T</b>	C8200L 1RU w/ 1 NIM slot and 4x 1 Gigabit Ethernet WAN ports	4	1 NIM 1 PIM	4 GB	No

\*16GB eUSB M.2 can only be ordered as a spare.

## Platform Performance

### Traffic patterns and use cases

**Table 3.** Cisco Catalyst 8300 Series SD-WAN performance

Feature	C8200-1N-4T	C8200L-1N-4T
SD-WAN IPsec Throughput (1400Bytes)	Up to 1Gbps	Up to 500Mbps
SD-WAN IPsec Throughput with IQDF** (1400Bytes)	Up to 1Gbps	Up to 460Mbps
SD-WAN IPsec Throughput (IMIX*)	900Mbps	400Mbps
SD-WAN IPsec Throughput with IQDF** (IMIX*)	850Mbps	300Mbps
SD-WAN Overlay Tunnels scale	2500	1500

\* IMIX is average packet size of 352 Bytes packet size

\*\* IQDF traffic pattern: IPsec + Quality of Service (QoS) + Deep Packet Inspection (DPI) + Flexible Netflow (FNF)

### SD-WAN Multi-layer security performance use cases

The Cisco Catalyst 8200 Series Edge platforms connect branch offices to the Internet and cloud, with industry-leading protection against major web attacks. Table 4 below provides test results for two common Multi-layer Security use cases in SD-WAN. Multi-layer Security use cases are only tested on C8200-1N-4T. C8200L-1N-4T doesn't support embedded, containerized, security features.

- The first use case is with 50% of the traffic encrypted in IQDF traffic pattern (IPsec + Quality of Service (QoS) + Deep Packet Inspection (DPI) + Flexible Netflow (FNF) and another 50% of unencrypted Direct Internet Access (DIA) traffic protected by advanced security features. This protection includes NG-FW, IPS, URLF (URL-Filtering) and AMP (Advanced Malware Protection).
- The second use case is with 100% unencrypted DIA traffic protected by the same advanced security features as in the first use case.

**Table 4.** Cisco Catalyst 8200-1N-4T SD-WAN, Multi-layer security performance use cases \*

Feature	C8200-1N-4T
50% IQDF* + 50% (DIA w. NAT + NGFW + IPS + URLF + AMP)	950Mbps
DIA w. NAT + NGFW + IPS + URLF + AMP	980Mbps

\* Tested with IOS XE release 17.12.2. All NGFW + UTD tests with Firewall EMIX traffic profile.

**Table 5.** Cisco Catalyst 8200 Series autonomous mode (non SD-WAN) performance specifications

Feature	C8200-1N-4T	C8200L-1N-4T
IPv4 Forwarding Throughput (1400Bytes)	Up to 3.8Gbps	Up to 3.8Gbps
IPsec Throughput (1400Bytes)	Up to 1Gbps	Up to 500Mbps
IPsec Throughput (IMIX*)	900Mbps	400Mbps

\* IMIX is average packet size of 352 Bytes packet size

**Table 6.** Cisco Catalyst 8300 Series autonomous mode (non SD-WAN) system scalability

Feature	C8200-1N-4T	C8200L-1N-4T
Number of IPsec SVTI Tunnels	2500	1500
Number of ACLs per system	4000	4000
Number of IPv4 ACEs per system	72K	72K
Number of IPv4 Routes	1.6M w/ default 8GB, up to 4M w/ 32GB	800k w/ default 4GB, up to 4M w/ 32GB
Number of IPv6 Routes	1.5M w/ default 8GB, up to 4M w/ 32GB	800k w/ default 4GB, up to 4M w/ 32GB
Number of Queues	16K	16K
Number of NAT Sessions	1.2M w/ default 8GB, up to 2M w/ 32GB	600k w/ default 4GB, up to 2M w/ 32GB
Number of Firewall Sessions	512K	512K
Number of VRFs	4000	4000

## Overall platform benefits

### Dynamic core allocation

Dynamic core allocation architecture will allow you to tailor the Cisco Catalyst 8200 Series Edge platforms’ multicore resources to fit your business needs. You can choose between two core allocations

- Service plane heavy mode is a service-oriented core allocation which has the platform’s Multicore resources set to balance throughput with providing adequate resources for containerized services. Choose Service plane heavy mode if integrated, container based, services are required. C8200-1N-4T with its 8-core SoC architecture will allow for KVM and/or Docker container-based applications on up to 3 cores. C8200L-1N-4T with a 4-core SoC architecture has a single core earmarked for Thousand Eyes agent in Service plane heavy mode. This platform doesn’t allow for KVM and/or Docker container-based applications. Service plane heavy mode is the factory default core allocation with which all C8200 platforms are shipped.

- 
- Data plane heavy core allocation has the platform’s Multicore resources repurposed and optimized for high traffic throughput. Choose this architecture when throughput is of higher priority, A Data plane heavy architecture will on 8-core platforms completely remove resources for containerized services.

In order to maximize the platforms performance and your investment, it’s recommended to change into a Data plane heavy core allocation when container-based services are not being required.

## **Accelerated services with Cisco Software-Defined WAN**

Cisco Catalyst SD-WAN is a set of intelligent software services that allow you to connect users, devices, and branch office locations reliably and securely across a diverse set of WAN transport links. The Cisco Catalyst 8000 Edge Platforms Family can dynamically route traffic across the “best” link based on up-to-the-minute application and network conditions for great application experiences. With Catalyst SD-WAN you get tight control over application performance, bandwidth usage, data privacy, and availability of your WAN links. This control is critical as branches conduct greater volumes of mission-critical business using both on-premises and cloud controllers.

## **SD-Routing**

### **Simplifying traditional routing deployment and workflows with Cisco Software-Defined Routing**

Cisco SD-Routing enables Cisco routing devices to be managed through Cisco Catalyst™ SD-WAN Manager, bringing operational simplicity and agility to traditional routing deployments by avoiding truck rolls for routine operational tasks. It also reduces OpEx by leveraging Catalyst SD-WAN Manager as the unified management platform for Catalyst SD-WAN as well as routing deployments.

SD-Routing enables customers to manage their routing devices in a flexible manner through on-premises controllers and will also be offered through cloud-delivered controllers in the near future.

Operationally, Cisco SD-Routing provides intuitive device lifecycle orchestration workflows for secure device onboarding as well as secure device software upgrades. By leveraging the rich monitoring and troubleshooting capabilities of Catalyst SD-WAN Manager, administrators can quickly isolate and resolve network problems.

## **Application performance optimization**

Ensure that SD-WAN networks meet Service-Level Agreements (SLAs) and maintain strong performance, even if network problems occur. With branch multicloud access, you can accelerate your Software-as-a-Service (SaaS) applications with a simple template push from the SD-WAN controller. Features such as TCP optimization, Forward Error Correction (FEC), and packet duplication enhance application performance for a better user experience.

## **Multilayer security**

You can now move your traditional and complex WAN networks into an agile, software-defined WAN with integrated security. The Catalyst 8200 Series Edge Platforms connect branch offices to the internet and cloud with industry-leading protection against major web attacks. Secure Direct Internet Access (DIA) from the branches helps optimize branch workloads for improved performance, specifically for cloud-hosted applications. At the same time, secure DIA helps ensure that your branch is protected from external threats.

## **Application visibility**

Applications and users are more distributed than ever, and the internet has effectively become the new enterprise WAN. As organizations continue to embrace internet, cloud, and SaaS, network and IT teams are challenged to deliver consistent and reliable connectivity and application performance over networks and services they don’t own or directly control.

---

The Catalyst 8200 Series Edge Platforms are integrated with Cisco ThousandEyes internet and cloud intelligence. IT managers now have expanded visibility, including hop-by-hop analytics, into network underlay, proactive monitoring of SD-WAN overlay, and performance measurement of SaaS applications. This granular visibility ultimately lowers the Mean Time to Identification of Issues (MTTI) and accelerates resolution time.

## **Unified communications**

The Catalyst 8200 Series Edge Platforms offer rich voice services in both SD-WAN and traditional Cisco IOS XE software feature stacks. Cisco is the only SD-WAN vendor to natively integrate analog and digital IP directly into single Customer Premises Equipment (CPE), reducing CapEx and OpEx. In SD-WAN mode, the Catalyst 8200 Series also helps prevent internal and external outages with Survivable Remote Site Telephony (SRST), enabling branch routers to assume the role of call control PBX for telephony survivability. They also continue to support a long list of traditional Cisco IOS XE voice use cases such as Cisco Unified Border Element (CUBE) Session Border Controller (SBC), Cisco Unified Communications Manager Express (CUCME), Survivable Remote Site Telephony (SRST), ISDN, and voice over IP.

## **Cloud-native agility with a programmable software architecture**

Cisco continues to offer a feature-rich traditional Cisco IOS XE routing stack on the Catalyst 8200 Series. IP routing, IPsec, QoS, firewall, NAT, Network-Based Application Recognition (NBAR), Flexible NetFlow (FNF), and many other features are part of Cisco IOS XE, a fully programmable software architecture with API support and a wide variety of protocols and configurations. With an integrated software image and a single binary file, you can now choose between Cisco IOS XE SD-WAN and Cisco IOS XE. And you can easily move from one to the other when you choose to do so.

## **Mobility**

The Catalyst 8200 Series Edge Platforms are built for high-speed Cat18 LTE and 5G networks. With the higher throughputs from Cat18 LTE and 5G, wireless WAN solutions are becoming feasible options for primary transport use cases. These platforms supports both integrated pluggable modules as well as external Cellular Gateways with Cat18 LTE and 5G capability for improved throughput that addresses those use cases. An integrated PIM module or external Cellular Gateway can be chosen based on a specific branch's cellular coverage, or work in tandem forming a high-availability Active-Active cellular WAN solution

## **Interface flexibility**

### **Layer 2 (Switched) and Layer 3 (Routed) ports**

The Catalyst 8200 Series continues Cisco's support for a flexible single-box solution with both switching and routing for a small branch. Layer 2 NIM modules provides 4- and 8-port switching with PoE capability and NIM based Layer 3 port modules provides extended Layer 3 port density in addition to the four embedded Layer 3 ports

### **LANWAN – Flexible L2 Switching and L3 Routing**

In addition to a wide range of NIM based Ethernet modules for a flexible and scalable combination of switched L2 ports and routed L3 ports, the Cisco Catalyst 8200 Series Edge Platforms also offer a new LANWAN module series which combines both capabilities. These new NIM based modules offers L2 and L3 ports of up to 2.5Gbps mGig with 90W PoE capacity and MACsec on all ports, plus full feature L3 capability on two ports. This provides a very high density of L3 ports and an unprecedented flexibility to the branch.



## Voice modules

The Catalyst 8200 Series continues Cisco's support for a variety of voice modules for the different voice needs at the branch. Voice module examples include Foreign Exchange Station (FXS), Foreign Exchange Office (FXO), Digital Signal Processor (DSP), etc.

## Sustainability

The Cisco Catalyst 8200 Series Edge Platforms are designed ground-up with sustainability in mind. These platforms are standardized on highly efficient power supplies and common form factors for sharing tooling and accessories. We have eliminated the use of plastic bezels as well as the need for wet paint, thereby reducing hazardous chemicals, and facilitating recyclability.

All platforms are designed for maximizing efficient use of PCBs and material in motherboard designs and for employing common modules across platforms. Over 70% of the ISR4000 platform family's modules are being reused by the Cisco Catalyst 8200 and 8300 Series Edge Platforms.

We standardize on integration of features to a single, very power effective, System on a Chip (SoC) architecture across the platform portfolio. It offers dynamic power management plus added power and thermal management capabilities on modules. All platforms furthermore include a barometer to sense atmospheric pressure and estimate installation altitude. Fan speeds can thereby be reduced in installations at lower altitudes, yielding significant energy savings.

## Throughput Efficiency (Gbps per Watt)

By using a single, effective, SoC architecture, the Cisco Catalyst 8200 Series Edge family provides significantly higher performance per consumed wattage than its predecessors.

## Supported modules

**Table 7.** Modules supported on Cisco Catalyst 8200 Series Edge Platforms

Product number	Description
<b>Ethernet Layer 3 modules</b>	
<b>C-NIM-1M</b>	1-port 2.5/1Gbps RJ-45 WAN, 90W Poe 802.3 af/at/bt NIM
<b>C-NIM-2T</b>	2-port 100Mbps/1Gbps dual-mode RJ45/SFP, NIM with WAN MACSec
<b>LAN / LANWAN modules</b>	
<b>C-NIM-8T</b>	8-port 100Mbps/1Gbps switch NIM, LAN/WAN MACSec and Optional L3
<b>C-NIM-8M*</b>	8-port 100M/1/2.5Gbps switch NIM, UPoE+, LAN/WAN MACSec and Optional L3
<b>NIM-ES2-4</b>	Cisco 4-port Gigabit Ethernet LAN switch NIM
<b>NIM-ES2-8</b>	Cisco 8-port Gigabit Ethernet LAN switch NIM
<b>NIM-ES2-8-P</b>	Cisco 8-port Gigabit Ethernet LAN switch NIM with PoE support
<b>Voice modules</b>	
<b>NIM-2FXO</b>	2-port FXO NIM

Product number	Description
<b>NIM-4FXO</b>	4-port FXO NIM
<b>NIM-2FXSP</b>	2-port FXS NIM
<b>NIM-4FXSP</b>	4-port FXS NIM
<b>NIM-2FXSP/4FXOP</b>	2-port FXS and 4-port FXO NIM
<b>NIM-4E/M</b>	4-port E/M NIM
<b>NIM-2BRI-NT/TE</b>	2-port BRI (NT and TE) NIM
<b>NIM-4BRI-NT/TE</b>	4-port BRI (NT and TE) NIM
<b>NIM-PVDM-32</b>	32-channel Voice DSP NIM Module
<b>NIM-PVDM-64</b>	64-channel Voice DSP NIM Module
<b>NIM-PVDM-128</b>	128-channel Voice DSP NIM Module
<b>NIM-PVDM-256</b>	256-channel Voice DSP NIM Module
<b>NIM-1MFT-T1/E1</b>	1-port multiflex trunk voice/clear-channel data T1/E1 module
<b>NIM-2MFT-T1/E1</b>	2-port multiflex trunk voice/clear-channel data T1/E1 module
<b>NIM-4MFT-T1/E1</b>	4-port multiflex trunk voice/clear-channel data T1/E1 module
<b>NIM-8MFT-T1/E1</b>	8-port multiflex trunk voice/clear-channel data T1/E1 module
<b>DSL/broadband</b>	
<b>NIM-VAB-A</b>	Multi-mode VDSL2/ADSL/2/2+ NIM Annex A
<b>NIM-VA-B</b>	Multi-mode VDSL2/ADSL/2/2+ NIM Annex B
<b>NIM-VAB-M</b>	Multi-mode VDSL2/ADSL/2/2+ NIM Annex M
<b>NIM-4SHDSL-EA</b>	Multi-mode G.SHDSL NIM
<b>ISDN BRI for Data</b>	
<b>NIM-2BRI-S/T</b>	2-port ISDN BRI WAN interface card for data
<b>NIM-4BRI-S/T</b>	4-port ISDN BRI WAN interface card for data
<b>Channelized T1/E1 and ISDN PRI</b>	
<b>NIM-1CE1T1-PRI</b>	1-port Multiflex trunk voice/channelized data T1/E1 module
<b>NIM-2CE1T1-PRI</b>	2-port Multiflex trunk voice/channelized data T1/E1 module
<b>NIM-8CE1T1-PRI</b>	8-port Multiflex trunk voice/channelized data T1/E1 module

Product number	Description
<b>Serial WAN interface</b>	
<b>NIM-1T</b>	1-port serial high-speed WAN interface card
<b>NIM-2T</b>	2-port serial high-speed WAN interface card
<b>NIM-4T</b>	4-port serial high-speed WAN interface card
<b>Async WAN interface</b>	
<b>NIM-16A</b>	16-port Asynchronous Module
<b>NIM-24A</b>	24-port Asynchronous Module
<b>Wireless WAN (LTE)</b>	
<b>P-5GS6-R16SA-GL*</b>	5G Sub-6 GHz Pluggable - 5G SA Global
<b>P-5GS6-GL</b>	5G Sub-6 GHz Pluggable - Global
<b>P-LTEAP18-GL</b>	CAT18 LTE Advanced Pro Pluggable - Global
<b>P-LTEA7-NA*</b>	CAT7 LTE Advanced Pluggable - North America
<b>P-LTEA7-EAL*</b>	CAT7 LTE Advanced Pluggable - EMEA, APAC, and LATAM
<b>P-LTEA7-JP*</b>	CAT7 LTE Advanced Pluggable - Japan
<b>P-LTEA-EA</b>	CAT6 LTE Advanced Pluggable - North America and EMEA
<b>P-LTEA-LA</b>	CAT6 LTE Advanced Pluggable - APAC, ANZ, and LATAM
<b>NIM-LTEA-EA</b>	CAT6 LTE Advanced - North America and EMEA
<b>NIM-LTEA-LA</b>	CAT6 LTE Advanced - APAC, ANZ, and LATAM

\* Supported with IOS-XE release 17.12.2

## Memory, storage, and accessory options

**Table 8.** Memory, storage, and accessory options

Product number	Description
<b>MEM-C8200-8GB</b>	Cisco C8200 Edge Platform - 8 GB DRAM Memory
<b>MEM-C8200-16GB</b>	Cisco C8200 Edge Platform - 16 GB DRAM Memory
<b>MEM-C8200-32GB</b>	Cisco C8200 Edge Platform - 32 GB DRAM Memory
<b>M2USB-16G</b>	Cisco C8000 Edge Platform - 16 GB M.2 USB SSD Storage
<b>M2USB-32G</b>	Cisco C8000 Edge Platform - 32 GB M.2 USB SSD Storage

Product number	Description
<b>SSD-M2NVME-600G</b>	Cisco C8000 Edge Platform - 600 GB M.2 NVMe SSD Storage
<b>SSD-M2SED-600G *</b>	Cisco C8000 Edge Platform - 600GB M.2 NVMe Self-Encrypted Drive (SED) Storage
<b>C8200-RM-19</b>	Cisco C8200 1RU Edge Platform - Rack Mount kit - 19"
<b>C8200-RM-23</b>	Cisco C8200 1RU Edge Platform - Rack Mount kit - 23"
<b>C8200-WM-1R</b>	Cisco C8200 1RU Edge Platform - Wall Mount Kit
<b>C8200-RFID-1R</b>	Cisco C8200 1RU Edge Platform - RFID
<b>C8200-NIM-BLANK</b>	Cisco C8200 NIM Blank
<b>C8200-PIM-BLANK</b>	Cisco C8200 PIM Blank

\* Supported with IOS-XE release 17.12.1

## Optics and transceivers modules

Find a full list of optics and transceivers [here](#).

## Power supplies

**Table 9.** Power supply specifications

Power supply feature	Default	PWR-CC1-150WAC optional external PSU for PoE
<b>Power maximum rating</b>	100W	150W For PoE only PoE budget: 150W
<b>Input-voltage range and frequency</b>	90 to 264 VAC 47 to 63 Hz	90 to 264 VAC 47 to 63 Hz
<b>Power supply efficiency</b>	85%	Avg 89%
<b>Input current</b>	1.5A max	2A max
<b>Output ratings</b>	12V 8.4A	54V 2.78A
<b>Output holdup time</b>	20 ms	10 ms
<b>Power supply input receptacles</b>	IEC 320 C14	IEC 320 C14
<b>Power cord rating</b>	10A	10A

**Table 10.** Cisco Catalyst 8200 Edge platform Typical power consumption

Power consumption, no modules	C8200-1N-4S	C8200L-1N-4S
Typical power (watts)	35W	33W

### Asset management

The Catalyst 8200 Series Edge Platforms have an embedded RFID tag that holds the serial number and product ID for easy asset and inventory management using commercial RFID readers. The RFID tag is external and can be easily removed if needed or can be unselected at the time of ordering. It also features an extendable label tag providing the same information. A QR code on this tag makes asset management easy by simply scanning the label using a smartphone QR reader.

### Software requirements

Cisco DNA Software for the Catalyst 8200 Series offers comprehensive solutions for enterprise branch networks.

**Table 11a.** Minimum software requirements

Platform product ID (PID)	Description	Minimum software requirement
C8200-1N-4T	Cisco Catalyst 8200 Series Edge Platform	Cisco IOS XE Software Release 17.4.1
C8200L-1N-4T	Cisco Catalyst 8200 Series Edge Platform	Cisco IOS XE Software Release 17.5.1

**Table 11b.** ThousandEyes requirements

Feature	Requirements
Cisco ThousandEyes	ThousandEyes is supported with a minimum 8 GB DRAM and 8 GB bootflash/storage. Additional memory and storage will be necessary for concurrently running the ThousandEyes agent with containerized SD-WAN security services.

**Table 11c.** Software features and protocols for autonomous mode

Feature	Description
Protocols	IPv4, IPv6, static routes, Routing Information Protocol Versions 1 and 2 (RIP and RIPv2), Open Shortest Path First (OSPF), Enhanced Interior Gateway Routing Protocol (EIGRP), Border Gateway Protocol (BGP), BGP Route Reflector, Intermediate System-to-Intermediate System (IS-IS), Multicast Internet Group Management Protocol Version 3 (IGMPv3), Protocol Independent Multicast Sparse Mode (PIM SM), PIM Source-Specific Multicast (SSM), Resource Reservation Protocol (RSVP), Cisco Discovery Protocol, Encapsulated Remote Switched Port Analyzer (ERSPAN), Cisco IOS IP Service-Level Agreements (IPSLA), Call Home, Cisco IOS Embedded Event Manager (EEM), Internet Key Exchange (IKE), ACLs, Ethernet Virtual Connections (EVC), Dynamic Host Configuration Protocol (DHCP), Frame Relay, DNS, Locator ID Separation Protocol (LISP), Hot Standby Router Protocol (HSRP), RADIUS, Authentication, Authorization, and Accounting (AAA), Application Visibility and Control (AVC), Distance Vector Multicast Routing Protocol (DVMRP), IPv4-to-IPv6 Multicast, Multiprotocol Label Switching (MPLS), Layer 2 and Layer 3 VPN, IPsec, Layer 2 Tunneling Protocol Version 3 (L2TPv3), Bidirectional Forwarding Detection (BFD), IEEE 802.1ag, and IEEE 802.3ah

Feature	Description
<b>Encapsulations</b>	Generic Routing Encapsulation (GRE), Ethernet, 802.1q VLAN, Point-to-Point Protocol (PPP), Multilink Point-to-Point Protocol (MLPPP), Frame Relay, Multilink Frame Relay (MLFR) (FR.15 and FR.16), High-Level Data Link Control (HDLC), serial (RS-232, RS-449, X.21, V.35, and EIA-530), and PPP over Ethernet (PPPoE)
<b>Traffic management</b>	QoS, Class-Based Weighted Fair Queuing (CBWFQ), Weighted Random Early Detection (WRED), Hierarchical QoS, Policy-Based Routing (PBR), and NBAR
<b>Cryptographic algorithms</b>	Encryption: Data Encryption Standard (DES), 3DES, Advanced Encryption Standard (AES)-128 or AES-256 (in Cipher Block Chaining [CBC] and Galois/Counter Mode [GCM]) Authentication: RSA (748/1024/2048 bit), ECDSA (256/384 bit) Integrity: MD5, SHA, SHA-256, SHA-384, SHA-512
<b>Unified communications</b>	Call Admission Control (CAC), Cisco Unified Boarder Element(CUBE) Session Border Controller(SBC), <b>Cisco Unified Communications Manager Express (CUCME), (ISDN), RADIUS</b> , RFC 4040-based clear channel codec signaling with Session Initiation Protocol (SIP), Resource Reservation Protocol (RSVP), RTP Control Protocol (RTCP), SIP for voice over IP (VoIP), Survivable Remote Site Telephony (SRST), Secure Real-Time Transport Protocol (SRTP), and voice modules

**Table 11d.** Software features and protocols for controller mode

Feature	Description
<b>Core features</b>	IPv4, IPv6, static routes, OSPF, EIGRP, BGP, Overlay Management Protocol (OMP), Application Aware Routing (AAR), Traffic Engineering, service insertion, zero trust, whitelisting, tamper-proof module, DTLS/TLS, IPsec, classification, prioritization, low latency queuing, remarking, shaping, scheduling, policing, mirroring, Multicast IPv4 support, service advertisement and insertion policy, Simple Network Management Protocol (SNMP), Network Time Protocol (NTP), DNS client, DHCP, DHCP client, DHCP server, DHCP relay archival, syslog, Secure Shell (SSH), Secure Copy (SCP), Cflowd v10 IPFIX export, IPv6 for transport side, Virtual Router Redundancy Protocol (VRRP), MPLS, NAT (DIA, service-side, overload/PAT, NAT64, etc.), NAT pools, split DNS, ACLs, BFD, NETCONF over SSH, CLI, NTP server support, BFD with service-side BGP, BGP community propagation to OMP, 6 SLA for AAR, Cisco TrustSec®/SD-Access (inline scalable group tag [SGT] propagation), custom app with Software-Defined AVC (SD-AVC), multicast AAR, dynamic on-demand tunnels, OSM, OSPFv3, route policies, multi-VRF support
<b>Encapsulations</b>	Generic Routing Encapsulation (GRE), Ethernet, 802.1q VLAN
<b>Application experience</b>	QoS, FEC, Class of Service (CoS) marking, Weighted Random Early Detection (WRED), Hierarchical QoS, PBR, NBAR, SD-AVC, per-tunnel QoS, Cloud OnRamp for SaaS, Enhanced Office 365 traffic steering, direct access, FNF
<b>Cryptographic algorithms</b>	Encryption: AES-256 (in CBC and GCM modes), Internet Key Exchange (IKE), Cisco Public Key Infrastructure (PKI) Authentication: AAA, RSA (2048 bit), ESP-256-CBC, HMAC-SHA1, ECDSA (256/384 bit) Integrity: SHA-1, SHA-2
<b>Security: C8200-1N-4T</b>	Built-in end-to-end segmentation (VPNs), zone-based firewall (ZBFW), PKI, Cisco DNA Layer Security, Snort® IPS/IDS, URL filtering, Secure Malware Defense, Secure Malware Analytics, Application-Level Gateway (ALG) for ZBFW, Secure Internet Gateway (SIG)
<b>Security: C8200L-1N-4T</b>	Built-in end-to-end segmentation (VPNs), ZBFW, PKI, Cisco DNA Layer Security, SIG

Feature	Description
<b>Unified communications</b>	Cisco Unified Border Element (CUBE), Survivable Remote Site Telephony (SRST), Cisco Unified Communications Manager Express (CUCME) and, voice modules

## Licensing

The Catalyst 8200 Series Edge Platforms are offered only with a Cisco DNA Software subscription, Enterprise Agreement, and Managed Service Licensing Agreement (MSLA). For more details, refer to this [licensing guide](#).

Cisco DNA Subscriptions offered with the Catalyst 8200 Series

- Catalyst Routing Essentials
- Cisco DNA Essentials
- Cisco DNA Advantage
- Cisco DNA Premier

For a more detailed overview on Cisco Licensing, go to [cisco.com/go/licensingguide](https://cisco.com/go/licensingguide).

## Cisco ThousandEyes

A valid ThousandEyes agent license is required to activate the ThousandEyes agent. Existing ThousandEyes subscriptions can be leveraged on eligible platforms. Additional ThousandEyes subscription information can be found [here](#).

## Specifications

**Table 12.** Mechanical specifications

Description	Specification
<b>Part number</b>	C8200-1N-4T and C8200L-1N-4T
<b>Dimensions (H x W x D)</b>	1.73 x 17.25 x 11.8 in. (4.39 x 43.81 x 29.97 cm)
<b>Rack Units (RU)</b>	1RU
<b>Chassis weight</b>	10 lb (4.54 kg)
<b>Input voltage</b>	AC: 90 to 264 VAC
<b>Operating temperature</b>	32° to 104°F (0° to 40°C)
<b>Storage temperature</b>	-40° to 150°F (-40° to 70°C)

Description	Specification
<b>Acoustics, both models:</b> <b>Sound pressure (Typical/maximum)</b>	54 dBA/69 dBA
<b>Acoustics, both models:</b> <b>Sound power (Typical/maximum)</b>	68 dBA/80 dBA
<b>Relative humidity operating and nonoperating noncondensing</b>	Ambient (noncondensing) operating: 5% to 85% Ambient (noncondensing) nonoperating and storage: 5% to 95%
<b>Altitude</b>	0 to 10,000 feet (0 to 3050 meters)
<b>Mean Time Between Failures (MTBF)</b>	692,577 hours

**Table 13.** Safety and compliance

Description	Specification
<b>Safety certifications</b>	UL 60950-1 CAN/CSA-C22.2 No. 60950-1 EN 60950-1 IEC 60950-1 AS/NZS 60950-1 IEC/EN 60825 Laser Safety FDA: Code of Federal Regulations Laser Safety
<b>EMC (emissions)</b>	47 CFR Part 15 Class A ICES 003 Class A AS/NZS CISPR 32 Class A CISPR 32 Class A EN55032 Class A VCCI-CISPR 32 Class A CNS-13438 Class A KN32 Class A IEC/EN 61000-3-2: Power Line Harmonics IEC/EN 61000-3-3: Voltage Fluctuations and Flicker



Description	Specification
<b>EMC (immunity)</b>	IEC/EN-61000-4-2: Electrostatic Discharge Immunity IEC/EN-61000-4-3: Radiated Immunity IEC/EN-61000-4-4: Electrical Fast Transient Immunity IEC/EN-61000-4-5: Surge AC, DC, and Signal Ports IEC/EN-61000-4-6: Immunity to Conducted Disturbances IEC/EN-61000-4-8: Power Frequency Magnetic Field Immunity IEC/EN-61000-4-11: Voltage DIPS, Short Interruptions, and Voltage Variations KN35
<b>EMC (ETSI/EN)</b>	EN300 386: Telecommunications Network Equipment (EMC) EN55032: Multimedia Equipment (Emissions) EN55024: Information Technology Equipment (Immunity) EN55035: Multimedia Equipment (Immunity) EN61000-6-1: Generic Immunity Standard

## Ordering information

To place an order, visit the [Cisco Ordering Home Page](#). To download software, visit the [Cisco Software Center](#).

## Product sustainability

Information about Cisco's environmental, Social and Governance (ESG) initiatives and performance is provided in Cisco's CSR and sustainability [reporting](#).

Sustainability Topic	Reference	
<b>General</b>	Information on product-material-content laws and regulations	<a href="#">Materials</a>
	Information on electronic waste laws and regulations, including our products, batteries and packaging	<a href="#">WEEE Compliance</a>
	Sustainability Inquiries	Contact: <a href="mailto:csr_inquiries@cisco.com">csr_inquiries@cisco.com</a>
	Information on product takeback and reuse program	<a href="#">Cisco Takeback and Reuse Program</a>
	Operating and nonoperating conditions	<a href="#">Table 12. Mechanical specifications</a>
	Mean Time Between Failures (MTBF)	<a href="#">Table 12. Mechanical specifications</a>
	Safety and EMC (emissions, immunity and ETSI/EN)	<a href="#">Table 12. Mechanical specifications</a>
<b>Power</b>	Power Supply	<a href="#">Table 1. Product highlights</a> <a href="#">Table 9. Power supply specifications</a>

Sustainability Topic		Reference
Material	Product packaging weight and materials	Contact: <a href="mailto:environment@cisco.com">environment@cisco.com</a>
	Dimensions and weight	<a href="#">Table 12. Mechanical specifications</a>

## Services

### Cisco Customer Experience support services for Catalyst 8000 platforms and Cisco DNA Software for SD-WAN and Routing

This section discusses the Cisco support services available for the Catalyst 8000 platforms and associated Cisco DNA Software for SD-WAN and Routing, as well as optional support service offers.

- **Catalyst 8000 platforms:** Cisco Solution Support is the default and recommended Cisco support service. However, Cisco Solution Support is not mandatory; it can be removed or replaced with another Cisco support service or partner service per the customer's preference.
- **Cisco DNA Software for SD-WAN and Routing:** Cisco Solution Support is the default Cisco support service. However, Cisco Solution Support is not mandatory; the customer may choose to use the Cisco Subscription Embedded Software Support included with the purchase of this software.

#### Note:

- When Solution Support is selected, it must be ordered on both the Catalyst 8000 platform and Cisco DNA Software for SD-WAN and Routing for complete customer entitlement to this premium support service.
- SD-WAN and Routing customers with Solution Support or Cisco Subscription Embedded Software Support are entitled to maintenance releases and software updates for **Cisco DNA SD-WAN and Routing software only**. Support for the Catalyst 8000 platform's OS and network stack, along with OS updates, is covered by the support contract on the Catalyst 8000 platform.
- For ThousandEyes support, C8200L-1N-4T must be upgraded to a minimum of 8GB DRAM

### Cisco Solution Support is a premium support purpose-built for today's multiproduct, multivendor network environments and provides:

- A primary point of contact, centralizing support across a solution deployment
- Solution, product, and interoperability expertise
- No requirement for customers to isolate their issue to a product to open a case
- 30-minute service response objective for Severity 1 and 2 cases
- Prioritized case handling over product support cases
- Product support team coordination (Cisco and Solution Support Alliance Partners)
- Accountability for multiproduct, multivendor issue management from first call to resolution, no matter where the issue resides

Learn more about Cisco Solution Support at: [www.cisco.com/go/solutionsupport](http://www.cisco.com/go/solutionsupport).

---

## Cisco Subscription Embedded Software Support includes:

- Access to support and troubleshooting via online tools and web case submission. Case severity or escalation guidelines are not applicable.
- Cisco Technical Assistance Center (TAC) access 24 hours per day, 7 days per week to assist by telephone, or web case submission and online tools with application software use and troubleshooting issues.
- Access to [www.cisco.com](http://www.cisco.com), providing helpful technical and general information on Cisco products, as well as access to Cisco's online Software Center library.

**Note:** No additional products or fees are required to receive embedded support for Cisco DNA Software for SD-WAN and Routing. However, if using embedded support for this software, hardware support for the Catalyst 8000 platforms must be purchased separately, as Cisco Subscription Embedded Software Support does not cover hardware. In this case, Cisco Smart Net Total Care<sup>®</sup> Service is recommended for the Catalyst 8000 platforms.

## Cisco Capital

### Flexible payment solutions to help you achieve your objectives

Cisco Capital<sup>®</sup> makes it easier to get the right technology to achieve your objectives, enable business transformation, and stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services and complementary third-party equipment in easy, predictable payments. [Learn more.](#)

## For more information

For more information about the Cisco Catalyst 8200 Series Edge Platforms, Visit: <https://www.cisco.com/go/C8200> or contact your local Cisco account representative.

---

## Document history

New or Revised Topic	Described In	Date
Updated licensing information	Licensing	June 25, 2021
Updated Technology and modules	Across document	April 22, 2024

**Americas Headquarters**  
Cisco Systems, Inc.  
San Jose, CA

**Asia Pacific Headquarters**  
Cisco Systems (USA) Pte. Ltd.  
Singapore

**Europe Headquarters**  
Cisco Systems International BV Amsterdam,  
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at <https://www.cisco.com/go/offices>.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)